NOLTR 66-146

ACOUSTIC IMPEDANCE OF SEA WATER AS A FUNCTION OF TEMPERATURE, PRESSURE AND SALINITY

19 JULY 1966

NOL

UNITED STATES NAVAL ORDNANCE LABORATORY, WHITE OAK, MARYLAND

NOLTR 66-146

NOLTR 66-146

ACOUSTIC IMPEDANCE OF SEA WATER AS A FUNCTION OF TEMPERATURE, PRESSURE AND SALINITY

by

David L. Bradley
and Wayne D. Wilson

Approved by
T. F. Johnston
Acoustics Division

ABSTRACT: The acoustic impedance (ρc) of sea water is presented as a function of temperature, pressure and salinity. This acoustic impedance has been calculated from empirical equations developed at the Naval Ordnance Laboratory to represent the velocity of sound and density of sea water as functions of the parameters temperature, pressure, and salinity. Tables of the calculated data and graphs are given.

Physics Research Department
U. S. Naval Ordnance Laboratory
White Oak, Silver Spring, Maryland

NOLTR 66-146 19 July 1966

Information on the acoustic properties of sea water is of continuing interest to the U. S. Navy. In anticipation of the future needs of the Fleet, information has been obtained on the extremes of temperature, pressure and salinity and various related acoustic properties likely to be needed in naval applications. The present work was funded under FR-27, "Structure of Liquids". This information will be useful to anyone computing the transmission properties of acoustic waves in sea water.



J. DARE
Captain, USN
Commander

Z. I. SLAWSKY
By direction

TABLE OF CONTENTS

LIST OF ILLUSTRATIONS

INTRODUCTION

The characteristic impedance of a medium for acoustic waves[1] is analogous to the index of refraction (n) of a transparent medium for light waves and to the wave impedance $\sqrt{\frac{\mu}{\varepsilon}}$ of a dielectric medium for electromagnetic waves. The product of the velocity of sound (c) and the density (ρ) provides a measurement of this characteristic impedance and is useful in the investigation of transmission phenomena of acoustic plane waves.

The results presented in this report were obtained from two empirical equations based on precision data taken at NOL. The first[2] represents sound velocity in sea water as a function of the three parameters: temperature, pressure and salinity. The second equation[3] represents the specific volume of sea water as a function of the same parameters. Both equations were developed to represent experimental data obtained from laboratory measurements. The product of the two, (c x 1/v), provides the acoustic impedance. The impedance data was calculated for the following parameter ranges: Temperature: $0^{o}C < T < 30^{o}C$, pressure: 1 bar < P < 1000 bars, salinity: 0‰ < S < 37‰. The bar as used in this report means 10^{6} dyne/cm^{2}.

THEORY

To avoid confusion, a brief summary of the various impedance terms is given. There are three kinds of acoustic impedances in common usage. First, the ratio of pressure to volume velocity, $\vec{Z}$ which is useful in discussing acoustic radiation from vibrating surfaces, and the transmission of this radiation through lumped acoustic elements at low frequencies. Second, the radiation impedance $\vec{Z}_r$, the ratio of force to velocity, is useful in calculating the coupling between acoustic waves and a driving source or driven load. It is part of the mechanical impedance of a vibrating system associated with the radiation of sound. Last, the specific acoustic impedance, is a characteristic property of the medium and of the type of waves that are being propagated through it. By definition, the complex ratio of acoustic pressure ($\vec{p}$) in a medium to the associated particle velocity ($\vec{u}$) is the specific acoustic impedance. In general

$$\vec{Z} = \frac{\vec{p}}{\vec{u}} = r + jx,$$

where $\vec{Z}$ = is a complex quantity. The term r is called the specific acoustic resistance and x the specific acoustic reactance of the medium for the particular wave motion being considered.

EQUATIONS

The equations representing the sound velocity and specific volume in sea water are empirical equations which were fitted to the laboratory experimental data. The coefficients of the equations were obtained by making a least squares fit to the experimental data on an IBM 7090 computer. Equation (1) can be used to calculate the sound velocity and Equation (2) the specific volume.

$$\begin{aligned} C = {} & 1449.14 + 4.5721\,T - 4.4532 \times 10^{-2} T^2 - 2.6045 \times 10^{-4} T^3 \\ & + 7.9851 \times 10^{-6} T^4 + 1.63431 \times 10^{-1} P + 1.0677 \times 10^{-5} P^2 \\ & + 3.7340 \times 10^{-9} P^{-3} - 3.6332 \times 10^{-12} P^4 + 1.39799\,(S-35.0) \\ & + 1.69202 \times 10^{-3}\,(S-35.0)^2 + (S-35.0)\,(-1.1244 \times 10^{-2} T \\ & + 7.7711 \times 10^{-7} T^2 + 7.8534 \times 10^{-5} P - 1.3458 \times 10^{-7} P^2 \\ & + 3.2202 \times 10^{-8} PT + 1.6101 \times 10^{-9} PT^2) + 1.01971\,P \\ & (-1.8607 \times 10^{-4} T + 7.4812 \times 10^{-6} T^2 + 4.5283 \times 10^{-8} T^3) \\ & + 1.03981\,P^2\,(-2.5294 \times 10^{-7} T + 1.8563 \times 10^{-9} T^2) \\ & + 1.06030\,P^3\,(-1.9646 \times 10^{-10} T) \end{aligned} \tag{1}$$

$$v = 0.7020 + \frac{1752.7286 + 11.001055T - 0.0639125T^2 - (3.9986175 + 0.010731021T)S}{P + 5880.9069 + 37.591888T - 0.343935T^2 + 2.2524542S} \tag{2}$$

The units of the various parameters are: Specific volume (cm^3/gm), sound velocity (m/sec), temperature (^oC), pressure (bars) and salinity (‰).

The standard deviations were computed from the expression

$$\sigma = \sqrt{\frac{\sum_{n=1}^{N} (x_e - x_c)^2}{N - k}} \tag{3}$$

where x_e and x_c are experimental and calculated data points respectively, N is the total number of data points and k the number of coefficients in the representative equation. For Equation (1) σ = 0.30 m/sec and for Equation (2) σ = 0.00013 cm^3/gm. These standard deviations show how well the empirical equations fit the experimental data. The equations are very convenient for machine computations since they provide analytic expressions for the data.

RESULTS

The results from the computations are shown in Tables I to V and also are presented graphically in Figs. 1 to 4.

REFERENCES

1. Kinsler and Frey, "Fundamentals of Acoustics", Wiley and Sons, New York (1950).

2. W. Wilson, J. Acoust. Soc. Am., 32, 1357 (1960).

3. W. Wilson and D. Bradley, NOLTR 66-103, 1-41 (1966).

TABLE I

Salinity = 0°/oo

Acoustic Impedance ($gm/cm^2 \cdot sec$)

P \ T	0°C	10°C	20°C	30°C
1 bar	$1.402 \times 10^{+5}$	$1.447 \times 10^{+5}$	$1.480 \times 10^{+5}$	$1.504 \times 10^{+5}$
100 "	1.426	1.470	1.503	1.527
200 "	1.449	1.493	1.526	1.550
300 "	1.473	1.517	1.550	1.574
400 "	1.498	1.540	1.573	1.597
500 "	1.522	1.564	1.597	1.621
600 "	1.547	1.589	1.621	1.644
700 "	1.572	1.613	1.644	1.668
800 "	1.598	1.638	1.668	1.691
900 "	1.624	1.662	1.692	1.715
1000 "	1.650	1.687	1.716	1.737

TABLE II

Salinity = 10°/oo

Acoustic Impedance ($gm/cm^2 \cdot sec$)

P \ T	0°C	10°C	20°C	30°C
1 bar	$1.427 \times 10^{+5}$	$1.470 \times 10^{+5}$	$1.502 \times 10^{+5}$	$1.525 \times 10^{+5}$
100 "	1.450	1.493	1.525	1.548
200 "	1.474	1.516	1.549	1.572
300 "	1.498	1.540	1.572	1.595
400 "	1.522	1.564	1.596	1.619
500 "	1.547	1.588	1.619	1.642
600 "	1.572	1.612	1.643	1.666
700 "	1.597	1.637	1.667	1.689
800 "	1.623	1.661	1.691	1.713
900 "	1.648	1.686	1.714	1.736
1000 "	1.674	1.710	1.738	1.758

TABLE III

Salinity = 20°/oo

Acoustic Impedance ($gm/cm^2 \cdot sec$)

P \ T	0°C	10°C	20°C	30°C
1 bar	$1.452 \times 10^{+5}$	$1.494 \times 10^{+5}$	$1.525 \times 10^{+5}$	$1.547 \times 10^{+5}$
100 "	1.475	1.517	1.548	1.570
200 "	1.499	1.540	1.571	1.593
300 "	1.523	1.564	1.595	1.617
400 "	1.548	1.588	1.618	1.640
500 "	1.572	1.612	1.642	1.664
600 "	1.597	1.636	1.666	1.688
700 "	1.623	1.661	1.690	1.711
800 "	1.648	1.685	1.714	1.734
900 "	1.674	1.710	1.737	1.757
1000 "	1.700	1.734	1.760	1.780

TABLE IV

Salinity = $30^{o}/oo$

Acoustic Impedance ($gm/cm^2 \cdot sec$)

P \ T	$0^{o}C$	$10^{o}C$	$20^{o}C$	$30^{o}C$
1 bar	$1.477 \times 10^{+5}$	$1.518 \times 10^{+5}$	$1.548 \times 10^{+5}$	$1.569 \times 10^{+5}$
100 "	1.501	1.541	1.571	1.592
200 "	1.525	1.565	1.595	1.616
300 "	1.549	1.589	1.618	1.639
400 "	1.574	1.613	1.642	1.663
500 "	1.598	1.637	1.666	1.686
600 "	1.623	1.661	1.690	1.710
700 "	1.649	1.686	1.713	1.734
800 "	1.674	1.710	1.737	1.757
900 "	1.700	1.734	1.760	1.780
1000 "	1.725	1.759	1.784	1.802

TABLE V

Salinity = $35^{o}/oo$

Acoustic Impedance ($gm/cm^2 \cdot sec$)

P \ T	$0^{o}C$	$10^{o}C$	$20^{o}C$	$30^{o}C$
1 bar	$1.490 \times 10^{+5}$	$1.531 \times 10^{+5}$	$1.560 \times 10^{+5}$	$1.580 \times 10^{+5}$
100 "	1.514	1.554	1.583	1.603
200 "	1.538	1.578	1.607	1.627
300 "	1.562	1.601	1.630	1.651
400 "	1.587	1.626	1.654	1.674
500 "	1.612	1.650	1.678	1.698
600 "	1.637	1.674	1.702	1.722
700 "	1.662	1.698	1.725	1.745
800 "	1.687	1.723	1.749	1.768
900 "	1.713	1.747	1.772	1.791
1000 "	1.739	1.771	1.796	1.813


1.880X10⁵
1.840
1.800
1.760
1.720
1.680
1.640
1.600
1.560
1.520
1.480
1.440
1.400
ACOUSTIC IMPEDANCE (GM/CM². SEC)
P = 1000 BARS
P = 900 BARS
P = 800 BARS
P = 700 BARS
P = 600 BARS
P = 500 BARS
P = 400 BARS
P = 300 BARS
P = 200 BARS
P = 100 BARS
P = 1 BAR
T = 0 °C
0
10
20
30
40
SALINITY (‰)

FIG. 1


1.880X10^5
1.840
1.800
1.760
1.720
1.680
1.640
1.600
1.560
1.520
1.480
1.440
1.400
ACOUSTIC IMPEDANCE (GM/CM^2. SEC)
P = 1000 BARS
P = 900 BARS
P = 800 BARS
P = 700 BARS
P = 600 BARS
P = 500 BARS
P = 400 BARS
P = 300 BARS
P = 200 BARS
P = 100 BARS
P = 1 BAR
T = 10 °C
0
10
20
30
40
SALINITY (‰)

FIG. 2


1.880 X10⁵
1.840
1.800
1.760
1.720
1.680
1.640
1.600
1.560
1.520
1.480
1.440
1.400
ACOUSTIC IMPEDANCE (GM/CM². SEC)
P = 1000 BARS
P = 900 BARS
P = 800 BARS
P = 700 BARS
P = 600 BARS
P = 500 BARS
P = 400 BARS
P = 300 BARS
P = 200 BARS
P = 100 BARS
P = 1 BAR
T = 20 °C
0
10
20
30
40
SALINITY (‰)

FIG 3


1.880X10^5
1.840
1.800
1.760
1.720
1.680
1.640
1.600
1.560
1.520
1.480
1.440
1.400
ACOUSTIC IMPEDANCE (GM/CM^2. SEC)
P = 1000 BARS
P = 900 BARS
P = 800 BARS
P = 700 BARS
P = 600 BARS
P = 500 BARS
P = 400 BARS
P = 300 BARS
P = 200 BARS
P = 100 BARS
P = 1 BAR
T = 30 °C
0
10
20
30
40
SALINITY (‰)

FIG. 4

UNCLASSIFIED
Security Classification

DOCUMENT CONTROL DATA - R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1 ORIGINATING ACTIVITY (Corporate author)

U. S. Naval Ordnance Laboratory

2a REPORT SECURITY CLASSIFICATION

Unclassified

2b GROUP

3 REPORT TITLE

Acoustic Impedance of Sea Water as a Function of Temperature, Pressure and Salinity

4 DESCRIPTIVE NOTES (Type of report and inclusive dates)

5 AUTHOR(S) (Last name, first name, initial)

Bradley, David L.

6 REPORT DATE	7a TOTAL NO OF PAGES	7b NO OF REFS
	14	3

8a CONTRACT OR GRANT NO	9a ORIGINATOR'S REPORT NUMBER(S)
b PROJECT NO MAT 03L 000/F011 01 01	NOLTR 66-146
c	9b OTHER REPORT NO(S) (Any other numbers that may be assigned this report)
d	

10 AVAILABILITY/LIMITATION NOTICES

Distribution of this Document is Unlimited.

11 SUPPLEMENTARY NOTES	12 SPONSORING MILITARY ACTIVITY

13 ABSTRACT

The acoustic impedance (ρc) of sea water is presented as a function of temperature, pressure and salinity. This acoustic impedance has been calculated from empirical equations developed at the Naval Ordnance Laboratory to represent the velocity of sound and density of sea water as functions of the parameters temperature, pressure, and salinity. Tables of the calculated data and graphs are given.

DD FORM 1 JAN 64 1473

UNCLASSIFIED
Security Classification

14 KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
Acoustic						
Impedance						
Sea Water						

INSTRUCTIONS

1. ORIGINATING ACTIVITY. Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization *(corporate author)* issuing the report.

2a. REPORT SECURITY CLASSIFICATION: Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. GROUP: Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. REPORT TITLE: Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. DESCRIPTIVE NOTES: If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. AUTHOR(S). Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. REPORT DATE. Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. TOTAL NUMBER OF PAGES: The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. NUMBER OF REFERENCES: Enter the total number of references cited in the report.

8a. CONTRACT OR GRANT NUMBER: If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. PROJECT NUMBER. Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. ORIGINATOR'S REPORT NUMBER(S). Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. OTHER REPORT NUMBER(S). If the report has been assigned any other report numbers *(either by the originator or by the sponsor)*, also enter this number(s).

10. AVAILABILITY/LIMITATION NOTICES: Enter any limitations on further dissemination of the report, other than those imposed by security classification, using standard statements such as:

(1) "Qualified requesters may obtain copies of this report from DDC."

(2) "Foreign announcement and dissemination of this report by DDC is not authorized."

(3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."

(4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."

(5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. SUPPLEMENTARY NOTES: Use for additional explanatory notes.

12. SPONSORING MILITARY ACTIVITY. Enter the name of the departmental project office or laboratory sponsoring *(paying for)* the research and development. Include address.

13. ABSTRACT: Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as *(TS) (S) (C) or (U)*.

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. KEY WORDS. Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, roles, and weights is optional.